





Gebrauchsanweisung
52 2707
(D,GB,F,I,NL)

Montageanleitung
52 2494
(D,GB,F,I,NL,DK,N,SF,
SE,TR)

Beistellsatz
26 5162

Temp.-Regler
Rep.-Satz
26 5271

Mat. – Nr. – Konstante
3740

	V01	V02	
Pos.	Matsushita	Goldstar	
	ESS 60E	NDA69NAEM	
1	14 2158	141999	
2			
3	18 3589	17 0743	
4			
5	18 3590	17 0745	
6	18 3591	17 0744	
7	16 9319	16 9319	
8	26 4879	26 4879	
9	05 0166	05 0166	
10			
11			
12			

TECHNISCHE DATEN / TECHNICAL DATA / DONNEES TECHNIQUES

Verdichter/Compressor/Compresseur	Matsushita	Goldstar	
Typ/Type	ESS 60E	NDA69NAEM	
Förderleistung/Delivery/Débit	l/h	1076	
Anlaufstrom/Starting current/Cour de démarrage	A	5,6	
Widerstand/Resistance/Résistance Ha/main/prin	Ω	30,6	
Hi/aux	Ω	26,7	
Temp.-Regler/Thermostat	KER		
Typ/Type	RCO		
Regelstellung/Position	kalt	warm	
Schaltwerte/Switching values	ein"	-23,0	-15,0
Valeurs de commutation	aus"	-31,0	-21,0
Füllmenge/Fill.quantity/Charge	R600a	*	
Anschlußwert/Conn.load/Puiss. connectée	W	63	
Heizung/Heater/Chauffage			
Widerstand/Resistance/Résistance	Ω		
Leistung/Power/Puissance	W		
Ventilator/Blower/Ventilateur			
Widerstand/Resistance/Résistance	Ω		
Temp.-Regler/Thermostat			
Magnetventil/Magnetic valve/Electrovanne			
Widerstand/Resistance/Résistance	Ω		
Spannung/Voltage/Tension	V		